

AC155 - LOW COST TRIAXIAL ACCELEROMETER, 100 MV/G, 4 PIN TOP EXIT CONNECTOR, FOR USE IN MODAL AND ODS ANALYSIS

AC155 - Kolmiakselinen edullinen kiihtyvyysanturi Modal/ODS sovelluksiin, 100 mV/g, 4 pin liitin päällä

MSP_VIRTUEMA CTC
RT_MANUFACT
URER

MSP_VIRTUEMA AC155
RT_SKU:

Tyyppi: 3-akselinen
Teollisuus

Herkkyys: 100 mV/g

Taajuusalue: 0.6-6500 Hz

Mittausalue: ± 50 g

Sovellukset: Condition Monitoring
Modal and ODS analysis

Tilausohje:



www.facebook.com/mipelectronics



www.linkedin.com/company/mip-electronics-ltd/



www.youtube.com/channel/UCpKEF_7bS4dMC4qPokUAgDQ

Ordering Information

Standard	AC155-1D (1/4-28 Captive Bolt) 
Metric	M/AC155-1D (M6x1 Captive Bolt) 

MSP_VIRTUEMART_TECHDETAILS

- Sensitivity: 100 mV/g
- Frequency Response (± 3 dB): 0.6-6500 Hz
- Dynamic Range: ± 50 g, peak
- Power Requirements Voltage Source: 18-30 VDC
- Temperature Range: -65 to 250°F
(-54 to 121°C)
- Case Material: 316L Stainless Steel
- Connector: 4 Pin J Connector
- Max Temp: 250°F (121°C)

MSP_VIRTUEMART_PRODDOCS

1. [Esite](http://www.mip.fi/images/docs/fi/1_vs_ac155_ds.pdf) , (URL: http://www.mip.fi/images/docs/fi/1_vs_ac155_ds.pdf)

MSP_VIRTUEMART_PRODUCT_IMAGE_TITLE



www.facebook.com/mipelectronics



www.linkedin.com/company/mip-electronics-ltd/



www.youtube.com/channel/UCpKEF_7bS4dMC4qPokUAgDQ



www.facebook.com/mipelectronics



www.linkedin.com/company/mip-electronics-ltd/



www.youtube.com/channel/UCpKEF_7bS4dMC4qPokUAgDQ



www.facebook.com/mipelectronics



www.linkedin.com/company/mip-electronics-ltd/



www.youtube.com/channel/UCpKEF_7bS4dMC4qPokUAgDQ