

AC192 - COMPACT, MULTI-PURPOSE ACCELEROMETER, TOP EXIT CONNECTOR / CABLE, 100 MV/G

AC192 - Kompakti, monikäyttöinen kiihtyvyysanturi, liitin/kaapeli päällä, 100 mV/g

MSP_VIRTUEMA CTC
RT_MANUFACT
URER

MSP_VIRTUEMA AC192
RT_SKU:

Tyyppi: 1-akselinen
Teollisuus

Herkkyys: 100 mV/g

Taajuusalue: 0.4-13000 Hz

Mittausalue: ± 80 g

Sovellukset: Condition Monitoring

Saatavissa 4 eri kokoonpanolla:

- 2 pin liittimellä AC192 - 1D
- Integroidulla kaapelilla AC192 - 2D
- Integroidulla suojatulla kaapelilla AC192 - 3D
- Integroidulla heavy duty suojatulla kaapelilla AC192 - 6D



www.facebook.com/mipelectronics




www.linkedin.com/company/mip-electronics-ltd/




www.youtube.com/channel/UCpKEF_7bS4dMC4qPokUAgDQ

AC192-1D


2 Pin Connector

**AC192-2D**


Integral Cable

**AC192-3D**

Armored Integral Cable

**AC192-6D**

Heavy Duty Armored Integral Cable

**MSP_VIRTUEMART_TechDETAILS**

- Sensitivity: 100 mV/g
- Frequency Response (± 3 dB): 0.4-13000 Hz
- Dynamic Range: ± 80 g, peak
- Power Requirements Voltage Source: 18-30 VDC
- Temperature Range: -58 to 250°F (-50 to 121°C)
- Case Material: 316L Stainless Steel
- Connector: 2 Pin MIL-C-5015
- Max Temp: 250°F (121°C)

MSP_VIRTUEMART_PRODDOCS

1. [Esite](http://www.mip.fi/images/docs/fi/1_vs_ac192_ds.pdf), (URL: http://www.mip.fi/images/docs/fi/1_vs_ac192_ds.pdf)

MSP_VIRTUEMART_PRODUCT_IMAGE_TITLE
www.facebook.com/mipelectronics

www.linkedin.com/company/mip-electronics-ltd/

www.youtube.com/channel/UCpKEF_7bS4dMC4qPokUAgDQ



www.facebook.com/mipelectronics



www.linkedin.com/company/mip-electronics-ltd/



www.youtube.com/channel/UCpKEF_7bS4dMC4qPokUAgDQ



www.facebook.com/mipelectronics



www.linkedin.com/company/mip-electronics-ltd/



www.youtube.com/channel/UCpKEF_7bS4dMC4qPokUAgDQ