

AC232 - PREMIUM MODAL/ODS TRIAXIAL ACCELEROMETER, CONNECTOR/CABLE, 10 MV/G, $\pm 5\%$

AC232 - Kolmiakselinen laadukas kiihtyvyysanturi Modal/ODS sovelluksiin, 10 mV/g, $\pm 5\%$

MSP_VIRTUEMA RT_MANUFACTURER CTC

MSP_VIRTUEMA RT_SKU: AC232

Tyyppi: 3-akselinen
Teollisuus

Herkkyys: 10 mV/g

Taajuusalue: 1.0-10000 Hz

Mittausalue: ± 500 g

Sovellukset: Condition Monitoring

Saatavissa 3 eri kokoonpanolla:

- 4 pin liittimellä AC232-1D
- integroidulla kaapelilla AC232-2D
- integroidulla metallikuorella suojatulla kaapelilla AC232-3D



www.facebook.com/mipelectronics



www.linkedin.com/company/mip-electronics-ltd/




www.youtube.com/channel/UCpKEF_7bS4dMC4qPokUAgDQ

AC232-1D

4 Pin Connector

		Asima DU Compatible	
Connector Pin	Polarity	Connector Pin	Polarity
A	Axis Y (-) Signal/Power	A	Axis 3 (-) Signal/Power
B	Axis X (-) Signal/Power	B	Axis 2 (-) Signal/Power
C	Axis Z (-) Signal/Power	C	Axis 1 (-) Signal/Power
D	(-) Common/Grid	D	(-) Common/Grid

**AC232-2D**


Integral Cable

		<u>Asima DU Compatible</u>	
Conductor	Polarity	Conductor	Polarity
Red	Axis Y (-) Signal/Power	Red	Axis 3 (-) Signal/Power
Green	Axis X (-) Signal/Power	Green	Axis 2 (-) Signal/Power
White	Axis Z (-) Signal/Power	White	Axis 1 (-) Signal/Power
Black	(-) Common/Grid	Black	(-) Common/Grid


**AC232-3D**

Armored Integral Cable

		Asima DU Compatible	
Conductor	Polarity	Conductor	Polarity
Red	Axis Y (-) Signal/Power	Red	Axis 3 (-) Signal/Power
Green	Axis X (-) Signal/Power	Green	Axis 2 (-) Signal/Power
White	Axis Z (-) Signal/Power	White	Axis 1 (-) Signal/Power
Black	(-) Common/Grid	Black	(-) Common/Grid



*Operating Deflection
Shape created from
vibration and phase
measurements.*

**MSP_VIRTUEMART_TECHDETAILS**

- Sensitivity: 10 mV/g
- Frequency Response ($\pm 3\text{dB}$): 1.0-10000 Hz
- Dynamic Range: ± 500 g, peak
- Power Requirements Voltage Source: 18-30 VDC
- Temperature Range: -65 to 250°F (-54 to 121°C)
- Case Material: 316L Stainless Steel
- Connector: 4 Pin J Connector
- Max Temp: 250°F (121°C)

MSP_VIRTUEMART_PRODDOCS

1. [Esite](http://www.mip.fi/images/docs/fi/1_vs_ac232_ds.pdf), (URL: http://www.mip.fi/images/docs/fi/1_vs_ac232_ds.pdf)

MSP_VIRTUEMART_PRODUCT_IMAGE_TITLE
www.facebook.com/mipelectronics

www.linkedin.com/company/mip-electronics-ltd/

www.youtube.com/channel/UCpKEF_7bS4dMC4qPokUAqDQ



www.facebook.com/mipelectronics



[www.linkedin.com/company/mip-electronics-ltd-/](https://www.linkedin.com/company/mip-electronics-ltd/)



www.youtube.com/channel/UCpKEF_7bS4dMC4qPokUAgDQ



www.facebook.com/mipelectronics



www.linkedin.com/company/mip-electronics-ltd-/



www.youtube.com/channel/UCpKEF_7bS4dMC4qPokUAgDQ