

DD100870 - 25 MM PRO PROXIMITY PROBE DRIVER FOR EDDY CURRENT PROBE, 4-20 MA OUTPUT

DD100870 - 25mm PRO-sarjan pyörrevirta-anturi ohjain, 4-20mA ulostulo

MSP_VIRTUEMA CTC
RT_MANUFACTURER

MSP_VIRTUEMA DD100870
RT_SKU:

Sovellukset: Liukulaakerin
kunnonvalvonta

Halkaisija: 25 mm

Tyyppi: 4-20 mA

Herkkyys: -0.787 V/mm

Saatavana erilaisilla kokoonpanoilla, kaikki asiakastilauksen pohjalta

STANDARD DRIVERS

ORDERING INFORMATION

DD1

Calibrated Material	Probe Type	Output Option	System Length	Mounting Type	Regulatory Approval
00 = 4140 Steel 08 = 1045 Steel 10 = 17-4 Stainless Steel 11 = 420 Stainless Steel 12 = 304 Stainless Steel 13 = 316 Stainless Steel 20 = 360 Brass Alloy 30 = AL7075-T	1 = 8 mm 7 = 11 mm 8 = 25 mm 9 = 5 mm FFv	70 = 4-20 mA 80 = Voltage	5 = 5.0 meter 7 = 7.0 meter (FFv only) 9 = 9.0 meter (non-FFv)	0 = Panel 1 = DIN	00 = CE Certified 05 = CSA, ATEX, IECEx, CE Approvals
Example Part Number: DD100170-91-00 4140 Steel, 8 mm probe, 4-20 mA output, 9.0 meter (non-FFv), DIN mount, CE Certified					

MSP_VIRTUEMART_TECHDETAILS



www.facebook.com/mipelectronics



www.linkedin.com/company/mip-electronics-ltd/



www.youtube.com/channel/UCpKEF_7bS4dMC4qPokUAgDQ

- Temperature Range: -31 to 185°F (-35 to 85°C)
- Linear Range: 25-525 mils (0.6 - 13.3 mm)
- Nominal Voltage Output: -20 mV/mil (-0.787 V/mm)
- Input Voltage: -17.5 VDC to -30 VDC
- Aluminum enclosure
- Miniature 12-32 threaded connector
- 4 Position screw terminals & BNC

MSP_VIRTUEMART_PRODDOCS

1. [Esite](http://www.mip.fi/images/docs/fi/pro_line_proximity_drivers.pdf) , (URL: http://www.mip.fi/images/docs/fi/pro_line_proximity_drivers.pdf)

MSP_VIRTUEMART_PRODUCT_IMAGE_TITLE



www.facebook.com/mipelectronics



www.linkedin.com/company/mip-electronics-ltd-/



www.youtube.com/channel/UCpKEF_7bS4dMC4qPokUAgDQ



www.facebook.com/mipelectronics



www.linkedin.com/company/mip-electronics-ltd/



www.youtube.com/channel/UCpKEF_7bS4dMC4qPokUAgDQ