

DX330851 - 25 MM BENTLY™ COMPATIBLE PROXIMITY PROBES

DX330851 - 25 mm Bently™ yhteensopiva pyörrevirta-anturi

MSP_VIRTUEMA CTC
RT_MANUFACTURER

MSP_VIRTUEMA DX330851
RT_SKU:

Sovellukset: Liukulaakerin
kunnonvalvonta

Halkaisija: 25 mm

Saatavilla usealla kokoonpanolla:

- Vakiokaapelilla tai suojatulla kaapelilla
- M30 asennuskierteellä
- Kaikki anturit asiakastilauksen pohjalta - katso esitteestä eri vaihtoehdot

Ordering Information

DX330851

0 1

AA

BB

CC

0 0



Case Thread	No Thread Length	Case Length	Total Length	Armor	Regulatory Approval
01 = 1 1/4-12	00 = 0.0 in 40 = 4.0 in	15 = 1.5 in 60 = 6.0 in	10 = 1.0 meter	00 = No Armor	00 = CE Certified
	05 = 0.5 in 50 = 5.0 in	20 = 2.0 in 70 = 7.0 in	50 = 5.0 meter	01 = Armor	
	10 = 1.0 in 60 = 6.0 in	30 = 3.0 in 80 = 8.0 in	90 = 9.0 meter	02 = No, with Connector Protector	
	20 = 2.0 in 70 = 7.0 in	40 = 4.0 in 95 = 9.5 in		03 = Yes, with Connector Protector	
	30 = 3.0 in 80 = 8.0 in	50 = 5.0 in			
	NOTE: 0.5 in. increments up to 1 in. less than the case length		NOTE: Highlighted lengths are stocked for shorter lead times		

Example Part Number: **DX33085101-05-15-10-00-00**

1 1/4-12 thread, 0.5 inch no thread length, 1.5 inch case length, 1.0 meter total length, no armor, CE certified

MSP_VIRTUEMART_TECHDETAILS

- Temperature Range: -49 to 212°F (-45 to 100°C)
- Material: FEP (Fluoroethylene Propylene) Jacket Cable Jacket with 316L Stainless Steel Probe



www.facebook.com/mipelectronics



www.linkedin.com/company/mip-electronics-ltd/



www.youtube.com/channel/UCpKEF_7bS4dMC4qPokUAqDQ

Body

MSP_VIRTUEMART_PRODDOCS

1. [Esite](http://www.mip.fi/images/docs/fi/dx330851.pdf), (URL: <http://www.mip.fi/images/docs/fi/dx330851.pdf>)

MSP_VIRTUEMART_PRODUCT_IMAGE_TITLE



www.facebook.com/mipelectronics



www.linkedin.com/company/mip-electronics-ltd-/



www.youtube.com/channel/UCpKEF_7bS4dMC4qPokUAgDQ



www.facebook.com/mipelectronics



www.linkedin.com/company/mip-electronics-ltd/



www.youtube.com/channel/UCpKEF_7bS4dMC4qPokUAgDQ