

DX991 - 5 MM BENTLY™ COMPATIBLE FFV PROXIMITY PROBE DRIVER FOR EDDY CURRENT PROBE, 4-20 MA AXIAL APPLICATIONS

DX991 - 5 mm mm Bently™-yhteensopiva kompakti FFv pyörrevirta-anturi ohjain, 4-20mA ulostulo, Axial Applications

MSP_VIRTUEMA CTC
RT_MANUFACTURER

MSP_VIRTUEMA DX991
RT_SKU:

Sovellukset: Liukulaakerin
kunnonvalvonta

Halkaisija: 5 mm

Tyyppi: 4-20 mA
axial

Saatavana erilaisilla kokoonpanoilla, kaikki asiakastilauksen pohjalta



www.facebook.com/mipelectronics



www.linkedin.com/company/mip-electronics-ltd-/



www.youtube.com/channel/UCpKEF_7bS4dMC4qPokUAgDQ

Ordering Information

DX991 - - - -

Full Scale	System Length	Mounting Type	Regulatory Approval
06 = 0.6-0-0.6 mm 25 = 25-0-25 mils	50 = 5.0 meter 70 = 7.0 meter	00 = Panel (Mounting Screws Are Not Included) 01 = DIN 02 = None	00 = CE Certified



Example Part Number: DX991-25-70-01-00

4140 Steel, 25-0-25 mils full scale, 7 meter system length, DIN mount, CE certified

MSP_VIRTUEMART_TechDETAILS

- Temperature Range: -31 to 185°F (-35 to 85°C)
- Material: Anodized Aluminum

MSP_VIRTUEMART_PRODDOCS

1. [Esite](http://www.mip.fi/images/docs/fi/6_pro_dx991_ds.pdf), (URL: http://www.mip.fi/images/docs/fi/6_pro_dx991_ds.pdf)

MSP_VIRTUEMART_PRODUCT_IMAGE_TITLE



www.facebook.com/mipelectronics



www.linkedin.com/company/mip-electronics-ltd/



www.youtube.com/channel/UCpKEF_7bS4dMC4qPokUAgDQ



www.facebook.com/mipelectronics



www.linkedin.com/company/mip-electronics-ltd/



www.youtube.com/channel/UCpKEF_7bS4dMC4qPokUAgDQ



www.facebook.com/mipelectronics



www.linkedin.com/company/mip-electronics-ltd-/



www.youtube.com/channel/UCpKEF_7bS4dMC4qPokUAgDQ