

HA602-A100 - CHARGE AMPLIFIER FOR USE WITH CM362 HIGH TEMPERATURE ACCELEROMETERS, 100 MV/G ACCELERATION OUTPUT

HA602-A100 - Varausvahvistin CM362-sarjankorkean lämpötilan kiihtyvyyssantureille, 100mV/g kiihtyvyyss tulostulo

MSP_VIRTUEMA CTC
RT_MANUFACTURER

MSP_VIRTUEMA HA602-A100
RT_SKU:

Tyyppi: 1-akselinen
Teollisuus
Korkea lämpötila 343 C

Herkkyys: 100 mV/g

Taajuusalue: N/A

Mittausalue: ± 50 g

Tilausohje:



www.facebook.com/mipelectronics



www.linkedin.com/company/mip-electronics-ltd/



www.youtube.com/channel/UCpKEF_7bS4dMC4qPokUAgDQ

Ordering Information

HA602 -

Output	
Charge Amplifier	A100 = 100 mV/g Acceleration Output
	V100 = 100 mV/in/sec Velocity Output
	A050 = 50 mV/g Acceleration Output

Example Part Number: HA602-A100
100 mV/g acceleration output

MSP_VIRTUEMART_TECHDETAILS

- Sensitivity: 100 mV/g
- Frequency Response (± 3 dB): N/A
- Dynamic Range: + - 50 g, peak
- Power Requirements Voltage Source: 18-30 VDC
- Temperature Range: -40 to 250°F
(-40 to 121°C)
- Case Material: 300 Series Stainless Steel
- Connector: 2 Pin MIL-C-5015
- Max Temp: 250°F
(121°C)

MSP_VIRTUEMART_PRODDOCS

1. [Esite](http://www.mip.fi/images/docs/fi/6_pro_ha602__2_ds.pdf) , (URL: http://www.mip.fi/images/docs/fi/6_pro_ha602__2_ds.pdf)

MSP_VIRTUEMART_PRODUCT_IMAGE_TITLE



www.facebook.com/mipelectronics



www.linkedin.com/company/mip-electronics-ltd/



www.youtube.com/channel/UCpKEF_7bS4dMC4qPokUAgDQ



www.facebook.com/mipelectronics



www.linkedin.com/company/mip-electronics-ltd/



www.youtube.com/channel/UCpKEF_7bS4dMC4qPokUAgDQ



www.facebook.com/mipelectronics



www.linkedin.com/company/mip-electronics-ltd/



www.youtube.com/channel/UCpKEF_7bS4dMC4qPokUAgDQ