

NORSONIC NOR265 - MIKROFONIN PYÖRITYSYKSIKKÖ

Pyörityskoneisto rakennusakustiikan ja äänitehotason mittauksiin.

Käyttökohteet

- Rakennusakustiikka
- Äänieristysmittaukset
- Äänitehotasojen mittaus kaiullisessa tilassa

MSP_VIRTUEMA Norsonic
RT_MANUFACTURER

MSP_VIRTUEMA NOR265
RT_SKU:

Nor265 on uudenaikainen pyörityskoneisto rakennusakustiikan ja äänitehotasojen mittauksiin. Sen ohjaus onnistuu myös PC:llä Nor850 järjestelmän kautta osana mittausjärjestelmää.

Ominaisuuksia:

- Vakiopyyhkäisyt +/- 90 ja +/- 180 astetta
- Käyttäjän mukaiset pyyhkäisyt ohjelmoitavissa ajan, kiihtyvyyden ja astekulmien suhteen
- PC-ohjaus RS-232-liittymällä
- Hiljainen pyörityskoneisto

MSP_VIRTUEMART_TECHDETAILS



www.facebook.com/mipelectronics



www.linkedin.com/company/mip-electronics-ltd/



www.youtube.com/channel/UCpKEF_7bS4dMC4qPokUAgDQ

Max sound level (re. 20 µPa): Diameter 202mm, Height: 171 mm

Size – main body: 6 kg

Mounting: Tripod allows inclined traverse plane

Diameter of tripod mounting stud: 3/8"

Main axle dimension: Outer diameter: 30 mm, Inner diameter: > 22 mm

Units to be mounted on turn axle:

Microphone boom (option 1)

Turn table (d=300 mm) (option 2)

Chuck (2 – 13 mm) (option 2)

Boom radius 0,8 – 2 m (continuously adjustable)

Rotation angle: -241592002° to +241592002° (more than 600.000 revolutions)

May also be set to rotate continuously at a specified direction and speed

Resolution: 0.01°

Angle accuracy (no torque): < 0.8°. Typical. < 0.05° if moved in one direction

Max load (any direction): 500 N

Max torque loading: 2 Nm

Typical error from loading torque: 0.3 deg/Nm

Power supply: 90 – 264V AC / 47 – 440 Hz

Fuses: 2,5 A slow blow (IEC 60127)

Remote operation (option 3): RS-232 interface: 9600 – 115200 baud

Noise emission: < 10 dBA at rest

< 23 dBA for all default rotations and sweep times (i.e. >20 sec/rev)

The noise is measured in an anechoic chamber with the moving microphone placed 1,5 m from the main body

Temperature range -10 to 50 °C

Humidity: 0 – 90 %RH

MSP_VIRTUEMART_PRODDOCS

1. [Esite](http://www.mip.fi/images/docs/fi/NOR265.pdf) , (URL: <http://www.mip.fi/images/docs/fi/NOR265.pdf>)

MSP_VIRTUEMART_PRODUCT_IMAGE_TITLE



www.facebook.com/mipelectronics



www.linkedin.com/company/mip-electronics-ltd-/



www.youtube.com/channel/UCpKEF_7bS4dMC4qPokUAgDQ



www.facebook.com/mipelectronics



www.linkedin.com/company/mip-electronics-ltd/



www.youtube.com/channel/UCpKEF_7bS4dMC4qPokUAgDQ



www.facebook.com/mipelectronics



www.linkedin.com/company/mip-electronics-ltd/



www.youtube.com/channel/UCpKEF_7bS4dMC4qPokUAgDQ