

TR104-M12A - DUAL OUTPUT, TEMPERATURE / ACCELERATION, SIDE EXIT M12 CONNECTOR / CABLE, 100 MV/G, 10 MV/°C

TR104-M12A - Dual Output, lämpötila ja kiihtyvyys, M12 liitin sivulla, 100 mV/g, 10 mV/°C

MSP_VIRTUEMA CTC
RT_MANUFACT
URER

MSP_VIRTUEMA TR104-M12A
RT_SKU:

Tyyppi: 1-akselinen
Teollisuus

Sovellukset: Condition Monitoring

- Base Mounted PT100 RTD Temperature Sensor
- Temperature and Acceleration in One Sensor
- 4 Pin M12 Connection

MSP_VIRTUEMART_TECHDETAILS

- Sensitivity: 100 mV/g
- Frequency Response (± 3 dB): 30-900,000 CPM
- Dynamic Range: ± 50 g, peak
- Power Requirements Voltage Source: 18-30 VDC
- Temperature Range: -40 to 250°F
- Case Material: 316L Stainless Steel
- Connector: 4 Pin M12
- Max Temp: 250°F (121°C)



www.facebook.com/mipelectronics



www.linkedin.com/company/mip-electronics-ltd/



www.youtube.com/channel/UCpKEF_7bS4dMC4qPokUAgDQ

MSP_VIRTUEMART_PRODDOCS

1. [Esite](http://www.mip.fi/images/docs/fi/tr104-m12a_datasheet.pdf), (URL: http://www.mip.fi/images/docs/fi/tr104-m12a_datasheet.pdf)

MSP_VIRTUEMART_PRODUCT_IMAGE_TITLE



www.facebook.com/mipelectronics



www.linkedin.com/company/mip-electronics-ltd-/



www.youtube.com/channel/UCpKEF_7bS4dMC4qPokUAgDQ



www.facebook.com/mipelectronics



www.linkedin.com/company/mip-electronics-ltd/



www.youtube.com/channel/UCpKEF_7bS4dMC4qPokUAgDQ