

TR102-M12A - DUAL OUTPUT, TEMPERATURE / ACCELERATION, TOP EXIT M12 CONNECTOR / CABLE, 100 MV/G, 10 MV/°C

TA102-M12A - Dual Output, lämpötila ja kiihtyvyys, M12 liitin päällä, 100 mV/g, 10 mV/C

MSP_VIRTUEMA CTC
RT_MANUFACTURER

MSP_VIRTUEMA TR102-M12A
RT_SKU:

Tyyppi: 1-akselinen
Teollisuus

Sovellukset: Condition Monitoring

Temperature Output 10 mV/°C High Performance in a Low Cost Sensor

Standard 3 Pin MIL

Connection Temperature and Acceleration in One Sensor

Affordably Priced

MSP_VIRTUEMART_TECHDETAILS

- Sensitivity: 100 mV/g
- Frequency Response ($\pm 3\text{dB}$): 30-900,000 CPM
- Dynamic Range: $\pm 50\text{g}$, peak
- Power Requirements Voltage Source: 18-30 VDC
- Temperature Range: -40 to 250°F



www.facebook.com/mipelectronics



[www.linkedin.com/company/mip-electronics-ltd-/](https://www.linkedin.com/company/mip-electronics-ltd/)



www.youtube.com/channel/UCpKEF_7bS4dMC4qPokUAgDQ

- Case Material: 316L Stainless Steel
- Connector: 4 Pin M12
- Max Temp: 250°F (121°C)

MSP_VIRTUEMART_PRODDOCS

1. [Esite](http://www.mip.fi/images/docs/fi/tr102-m12a_datasheet.pdf) , (URL: http://www.mip.fi/images/docs/fi/tr102-m12a_datasheet.pdf)

MSP_VIRTUEMART_PRODUCT_IMAGE_TITLE



www.facebook.com/mipelectronics



www.linkedin.com/company/mip-electronics-ltd-/



www.youtube.com/channel/UCpKEF_7bS4dMC4qPokUAgDQ



www.facebook.com/mipelectronics



www.linkedin.com/company/mip-electronics-ltd/



www.youtube.com/channel/UCpKEF_7bS4dMC4qPokUAgDQ