

UEB330 ULTRASOUND SENSOR, 100MV/G

Ultrasound Sensor, 100mV/g, Top Exit, 2 Pin mini-MIL Connector, 1/4-28 Mounting

MSP_VIRTUEMA	CTC
RT_MANUFACTURER	
MSP_VIRTUEMA	UEB330
RT_SKU:	
Tyyppi:	1-akselinen Teollisuus
Herkkyys:	100 mV/g
Taajuusalue:	0 5-25000 Hz
Mittausalue:	± 50 g

- High Frequency Ultrasound Accelerometer
- High Amplitude Resonance Peak for Stress Wave Measurement Techniques
- IEPE Amplifier Technology

MSP_VIRTUEMART_TECHDETAILS

- Sensitivity: 100 mV/g
- Frequency Response ($\pm 3\text{dB}$): 30-1,500,000 CPM
- Dynamic Range: $\pm 50\text{g}$, peak
- Power Requirements Voltage Source: 18-30 VDC
- Temperature Range: -58 to 250°F
- Case Material: 316L Stainless Steel
- Connector: 2 Pin mini-MIL, J Series Connector
- Max Temp: 250°F (121°C)

MSP_VIRTUEMART_PRODDOCS

1. [Esite](http://www.mip.fi/images/docs/fi/ueb330_datasheet.pdf), (URL: http://www.mip.fi/images/docs/fi/ueb330_datasheet.pdf)



www.facebook.com/mipelectronics



www.linkedin.com/company/mip-electronics-ltd/



www.youtube.com/channel/UCpKEF_7bS4dMC4qPokUAgDQ

MSP_VIRTUEMART_PRODUCT_IMAGE_TITLE



www.facebook.com/mipelectronics



www.linkedin.com/company/mip-electronics-ltd-/



www.youtube.com/channel/UCpKEF_7bS4dMC4qPokUAgDQ



www.facebook.com/mipelectronics



www.linkedin.com/company/mip-electronics-ltd/



www.youtube.com/channel/UCpKEF_7bS4dMC4qPokUAgDQ