

# VE136 - PIEZO VELOCITY SENSOR, SIDE EXIT CONNECTOR / CABLE, 20 MV/MM/SEC

VE136 - Nopeusanturi, liitäntä sivulta/kaapelilla, 20 mV/mm/sec

MSP\_VIRTUEMA CTC  
RT\_MANUFACTURER

MSP\_VIRTUEMA VE136  
RT\_SKU:

Tyyppi: 1-akselinen  
Teollisuus

Herkkyys: 20 mV/mm/sec

Taajuusalue: 1-7  
000 Hz

Mittausalue:  $\pm 254$  mm/sec. pk

Sovellukset: Condition Monitoring

Tilausohje:

## Ordering Information

| Standard | VE136-1A<br>(1/4-28<br>Captive<br>Bolt) | VE136-2C - /<br>(1/4-28<br>Captive<br>Bolt) | VE136-3C - /<br>(1/4-28<br>Captive<br>Bolt)                        | VE136-6C - /<br>(1/4-28<br>Captive<br>Bolt)                       |
|----------|-----------------------------------------|---------------------------------------------|--------------------------------------------------------------------|-------------------------------------------------------------------|
|          | Stock Product                           | Build To Order                              | Build To Order                                                     | Build To Order                                                    |
|          |                                         | (length in feet) (termination)              | (maximum armor length 100 ft) (cable length in feet) (termination) | (maximum armor length 20 ft) (cable length in feet) (termination) |
| Metric   | M/VE136-1A<br>(M6x1<br>Captive<br>Bolt) | M/VE136-2C - /<br>(M6x1<br>Captive<br>Bolt) | M/VE136-3C - /<br>(M6x1<br>Captive<br>Bolt)                        | M/VE136-6C - /<br>(M6x1<br>Captive<br>Bolt)                       |
|          | Stock Product                           | Build To Order                              | Build To Order                                                     | Build To Order                                                    |
|          |                                         | (length in feet) (termination)              | (maximum armor length 100 ft) (cable length in feet) (termination) | (maximum armor length 20 ft) (cable length in feet) (termination) |
|          |                                         | (length in meters) (termination)            | (maximum armor length 30 m) (cable length in meters) (termination) | (maximum armor length 6 m) (cable length in meters) (termination) |

Cable Termination Options: E  F  L  Z 

## MSP\_VIRTUEMART\_TECHDETAILS

- Sensitivity: 20 mV/mm/sec
- Frequency Response ( $\pm 3$ dB): 1.0 - 7000 Hz
- Dynamic Range:  $\pm 254$  mm/sec. pk
- Power Requirements Voltage Source: 18-30 VDC
- Temperature Range: -58 to 250°F (-50 to 121°C)
- Case Material: 316L Stainless Steel
- Connector: 2 Pin MIL-C-5015
- Max Temp: 250°F (121°C)



[www.facebook.com/mipelectronics](https://www.facebook.com/mipelectronics)



[www.linkedin.com/company/mip-electronics-ltd/](https://www.linkedin.com/company/mip-electronics-ltd/)



[www.youtube.com/channel/UCpKEF\\_7bS4dMC4qPokUAgDQ](https://www.youtube.com/channel/UCpKEF_7bS4dMC4qPokUAgDQ)

## MSP\_VIRTUEMART\_PRODDOCS

1. [Esite](http://www.mip.fi/images/docs/fi/1_vs_ve136_ds.pdf), (URL: [http://www.mip.fi/images/docs/fi/1\\_vs\\_ve136\\_ds.pdf](http://www.mip.fi/images/docs/fi/1_vs_ve136_ds.pdf))

## MSP\_VIRTUEMART\_PRODUCT\_IMAGE\_TITLE

[www.facebook.com/mipelectronics](https://www.facebook.com/mipelectronics)[www.linkedin.com/company/mip-electronics-ltd-/](https://www.linkedin.com/company/mip-electronics-ltd-/)[www.youtube.com/channel/UCpKEF\\_7bS4dMC4qPokUAgDQ](https://www.youtube.com/channel/UCpKEF_7bS4dMC4qPokUAgDQ)



[www.facebook.com/mipelectronics](https://www.facebook.com/mipelectronics)



[www.linkedin.com/company/mip-electronics-ltd/](https://www.linkedin.com/company/mip-electronics-ltd/)



[www.youtube.com/channel/UCpKEF\\_7bS4dMC4qPokUAgDQ](https://www.youtube.com/channel/UCpKEF_7bS4dMC4qPokUAgDQ)