

VT104 - DUAL OUTPUT PIEZO VELOCITY SENSOR, 4MV/MM/SEC, WITH TEMPERATURE OUTPUT, 10 MV/°C, SIDE EXIT CONNECTOR

VT104 - Dual Output kiihtyvyyssanturi, 4mV/mm/sec, lämpötila ulostulo 10 mV/°C, liitin/kaapeli sivulla

MSP_VIRTUEMA CTC
RT_MANUFACT
URER

MSP_VIRTUEMA VT104
RT_SKU:

Tyyppi: 1-akselinen
Teollisuus

Herkkyys: 4 mV/mm/sec

Taajuusalue: 1.5-7000 Hz

Mittausalue: ±1270 mm/sec. pk

Sovellukset: Condition Monitoring

Tilausohje:

Ordering Information

Standard	VT104-1D (1/4-28 Captive Bolt) Stock Product	VT104-2D / (1/4-28 Captive Bolt) Build To Order (length in feet) (termination)	VT104-3D / (1/4-28 Captive Bolt) Build To Order (maximum armor length 100 ft) (cable length in feet) (termination)
Metric	M/VT104-1D (M6x1 Captive Bolt) Stock Product	M/VT104-2D / (M6x1 Captive Bolt) Build To Order (length in feet) (termination) (length in meters) (termination)	M/VT104-3D / (M6x1 Captive Bolt) Build To Order (maximum armor length 100 ft) (cable length in feet) (termination) (maximum armor length 30 m) (cable length in meters) (termination)

Cable Terminations: L  Z

MSP_VIRTUEMART_TECHDETAILS



www.facebook.com/mipelectronics



www.linkedin.com/company/mip-electronics-ltd/



www.youtube.com/channel/UCpKEF_7bS4dMC4qPokUAGDQ

- Sensitivity: 4mV/mm/sec
- Frequency Response (± 3 dB): 1.5-7000 Hz
- Dynamic Range: ± 1270 mm/sec. pk
- Power Requirements Voltage Source: 18-30 VDC
- Temperature Range: -58 to 250°F (-50 to 121°C)
- Case Material: 316L Stainless Steel
- Connector: 3 Pin MIL-C-5015
- Max Temp: 250°F (121°C)

MSP_VIRTUEMART_PRODDOCS

1. [Esite](http://www.mip.fi/images/docs/fi/1_vs_vt104_ds.pdf) , (URL: http://www.mip.fi/images/docs/fi/1_vs_vt104_ds.pdf)

MSP_VIRTUEMART_PRODUCT_IMAGE_TITLE



www.facebook.com/mipelectronics



www.linkedin.com/company/mip-electronics-ltd-/



www.youtube.com/channel/UCpKEF_7bS4dMC4qPokUAgDQ



www.facebook.com/mipelectronics



www.linkedin.com/company/mip-electronics-ltd/



www.youtube.com/channel/UCpKEF_7bS4dMC4qPokUAgDQ