

WT203

Kiihtyvyyssanturi tarkoitettu tuuliturbiini/tuulivoimala-ympäistöön. 0.1 - 10.000Hz ,
Top Exit Connector, 100 mV/g

MSP_VIRTUEMA	CTC
RT_MANUFACTURER	
MSP_VIRTUEMA	WT203
RT_SKU:	
Tyyppi:	1-akselinen Tuulivoima
Herkkyys:	100 mV/g
Taajuusalue:	0.5 - 10 000 Hz
Mittausalue:	± 80 g
Sovellukset:	Condition Monitoring

Product Features

Designed for Machinery Applications in which Low and High Frequency Conditions May Exist

- 100 mV/g Sensitivity ±10%
- 0.1 Hz for Low Frequency Measurements
- 10,000 Hz for High Frequency Detection

MSP_VIRTUEMART_TECHDETAILS

- Sensitivity: 100 mV/g
- Frequency Response (±3dB): 6-600,000 CPM
- Dynamic Range: ± 80g, peak
- Power Requirements Voltage Source: 18-30 VDC
- Temperature Range: -58 to 250°F
- Case Material: 316L Stainless Steel
- Connector: 2 Pin MIL-C-5015
- Max Temp: 250°F (121°C)

MSP_VIRTUEMART_PRODDOCS



www.facebook.com/mipelectronics



www.linkedin.com/company/mip-electronics-ltd-/



www.youtube.com/channel/UCpKEF_7bS4dMC4qPokUAgDQ

1. [Esite](http://www.mip.fi/images/docs/fi/wt203_datasheet.pdf), (URL: http://www.mip.fi/images/docs/fi/wt203_datasheet.pdf)

MSP_VIRTUEMART_PRODUCT_IMAGE_TITLE



www.facebook.com/mipelectronics



[www.linkedin.com/company/mip-electronics-ltd-/](https://www.linkedin.com/company/mip-electronics-ltd/)



www.youtube.com/channel/UCpKEF_7bS4dMC4qPokUAgDQ



www.facebook.com/mipelectronics



www.linkedin.com/company/mip-electronics-ltd/



www.youtube.com/channel/UCpKEF_7bS4dMC4qPokUAgDQ