

48LX-8 UTP LINE-ARRAY, 4/8 CHANNEL, MEDIUM PRESSURE

4- tai 8-linjan ultra ohut tarkkuusmikrofoni, jossa yhdistyy perinteisen mittausmikrofonin kyvykkyydet ja 1,35 mm paksuus. Maailman ohuin kondensaattorimikrofoni linja.

Valmistaja:	GRAS
Tuotenumero:	48LX-4/8
Herkkyys:	0.6 mv/Pa
Taajuusalue:	10 hz - 70 kHz
Dynaaminen alue:	54 - 170 dB
Tyyppi:	Ultra thin mikrofonit

FLAT - FAST - PRECISE

The World's Thinnest Condenser Microphones

Laminaarisen ja turbulentin ilmvirran akustiset mittaukset edellyttävät matalaproofilisia antureita äänikentän häiriöiden minimoiseksi.

Siksi olemme GRAS: ssa kehittäneet UTP-mikrofonit - Ultra Thin Precision -mikrofonit. Ne yhdistävät klassisen mittausmikrofonin edut - laaja taajuusalue, tarkkuus ja toistettavuus - erittäin pieneen kokoon.

GRAS 48LX-4/8 on vain 1 mm korkea, ja siksi se on ihanteellinen mittauksiin pintarakenteissa ja turbulenssissa.

EXPLORE THE BENEFITS

The very small things which make the BIG difference

Quality Data

UTP provides accurate data from precision measurement microphones manufactured to narrow specifications. All LX-versions have TEDS.

Low Profile

With a height of 1,35 mm the door to a whole new world of what can be measured in boundary layers and turbulent flow opens.

Easy Mounting and Verification

As described below, mounting is easy with masking tape, and once mounted, the setup can easily and quickly be verified in-situ, a major advantage when you want to check the integrity of your measurement setup.

Small Form Factor and Simplified Cabling

48LX-4/8 can be used in small or difficult-to-access spaces where conventional microphones must give up. Easy connection and cabling.

Cost-saving Solution

Easy mounting, CCP interface with integral cabling and in-situ verification all add up to reduced setup time and faster measurements - with reliable data.

Flow-optimized Fairings

Fairings with a rise angle of 6.5 ensure minimal disturbance to the sound field/airflow.

Easy Mounting and In-Situ Verification

48LX-4/8 is easy to mount and remove.

It can be mounted using masking tape.

Fast and reliable in-situ verification saves time and increases confidence.

A special verification adapter with a soft cushion allows for quick, easy, and reliable in-situ verification. Four distance spacers ensure that the correct volume is achieved and that this volume can easily be reproduced. Even on curved surfaces, this verification method is so precise that dismounting is not necessary.



&NBSP;

Tekniset tiedot

Specifications

Frequency range (± 1 dB)	Hz	20 to 20 k
Frequency range (± 3 dB)	Hz	16 to 31.5 k
Dynamic range lower limit (microphone thermal noise)	dB(A)	64
Dynamic range upper limit	dB	184
Set sensitivity @ 250 Hz (± 2 dB)	mV/Pa	0.12
Set sensitivity @ 250 Hz (± 2 dB)	dB re 1V/Pa	-78.4
Output impedance	Ω	<50
Power supply min. to max.	mA	2 to 10
Microphone venting		Front
Temperature range, operation	$^{\circ}\text{C}$ / $^{\circ}\text{F}$	-20 to 85 / -4 to 185
Temperature range, storage	$^{\circ}\text{C}$ / $^{\circ}\text{F}$	-40 to 85 / -40 to 185
Temperature coefficient @250 Hz	dB/ $^{\circ}\text{C}$ / dB/ $^{\circ}\text{F}$	-0.03
Static pressure coefficient @250 Hz	dB/kPa	-0.0003
Humidity range non condensing	% RH	0 to 80
Humidity coefficient @250 Hz	dB/% RH	-0.01
Influence of axial vibration @1 m/s ²	dB re 20 μPa	73
Connector type		Microdot 10/32
Weight	g / oz	1 / 0.035 (excl. cable) 4 / 0.14 (incl. cable)

Toimitussisältö

- Gras 48 LX 4/8 UTP mikrofoni, medium Pressure, 3 metrin kaapelilla
- Asennusteippi
- Kalibrointitodistus

Dokumentit

1. [Esite UTP mikrofoni](http://www.mip.fi/images/docs/fi/utp-auto_brochure_v72.pdf), (URL: http://www.mip.fi/images/docs/fi/utp-auto_brochure_v72.pdf)
2. [Esite 48LX 4/8](http://www.mip.fi/images/docs/fi/gras_48lx-8.pdf), (URL: http://www.mip.fi/images/docs/fi/gras_48lx-8.pdf)

Lisäkuvat ja videot

