

AC132 - LOW COST TRIAXIAL ACCELEROMETER, FOR MODAL & ODS ANALYSIS, CONNECTOR/CABLE, 10 MV/G

AC132 - Edullinen kolmi-akselinen kiihtyvyyssanturi, Modal & ODS analysointiin, liitin/kaapeli sivulla, 10 mV/g


Valmistaja:	CTC
Tuotenumero:	AC132
Tyyppi:	3-akselinen Teollisuus
Herkkyys:	10 mV/g
Taajuusalue:	1-8000 Hz
Mittausalue:	± 500 g
Sovellukset:	Kunnonvalvonta Moodi- ja ODS analyysi

Saatavissa kolmella eri kokoonpanolla:

AC132-1D

4 Pin Connector


Connector Pin	Polarity	Azima DU Compatible	Connector Pin	Polarity
A	Axis Y (+) Signal/Power		A	Axis 3 (+) Signal/Power
B	Axis X (+) Signal/Power		B	Axis 2 (+) Signal/Power
C	Axis Z (+) Signal/Power		C	Axis 1 (+) Signal/Power
D	(-) Common/Grd		D	(-) Common/Grd



AC132-2D

Integral Cable


Conductor	Polarity	Azima DU Compatible	Conductor	Polarity
Red	Axis Y (+) Signal/Power		Red	Axis 3 (+) Signal/Power
Green	Axis X (+) Signal/Power		Green	Axis 2 (+) Signal/Power
White	Axis Z (+) Signal/Power		White	Axis 1 (+) Signal/Power
Black	(-) Common/Grd		Black	(-) Common/Grd




AC132-3D

Armored Integral Cable

Conductor	Polarity	Azima DU Compatible	Conductor	Polarity
Red	Axis Y (+) Signal/Power		Red	Axis 3 (+) Signal/Power
Green	Axis X (+) Signal/Power		Green	Axis 2 (+) Signal/Power
White	Axis Z (+) Signal/Power		White	Axis 1 (+) Signal/Power
Black	(-) Common/Grd		Black	(-) Common/Grd



Operating Deflection Shape created from vibration and phase measurements.



Tekniset tiedot

- Sensitivity: 10 mV/g
- Frequency Response (±3dB): 1-8000 Hz

- Dynamic Range: ± 500 g, peak
- Power Requirements Voltage Source: 18-30 VDC
- Temperature Range: -58 to 250°F
(-50 to 121°C)
- Case Material: 316L Stainless Steel
- Connector: 4 Pin J Connector
- Max Temp: 250°F
(121°C)

Dokumentit

1. [Esite](http://www.mip.fi/images/docs/fi/1_vs_ac132_ds.pdf) , (URL: http://www.mip.fi/images/docs/fi/1_vs_ac132_ds.pdf)