

TA935 - CLASS 1, DIVISION 2/ZONE 2 DUAL OUTPUT SENSOR, ACCELERATION AND TEMPERATURE, 100 MV/G, 10 MV/°C, 3 PIN TOP EXIT CONNECTOR

TA935 - Class 1, Division 2/Zone 2 Dual Output anturi, kiihtyvyyys ja lämpötila, 100 mV/g, 10 mV/°C, 3 Pin liitin/kaapeli päällä

Valmistaja:	CTC
Tuotenumero:	TA935
Tyyppi:	1-akselinen Teollisuus Sovellukset: Atex Zone 2
Herkkyys:	100 mV/g
Taajuusalue:	0.5-15000 Hz
Mittausalue:	± 80 g

Tilausohje:

Ordering Information

Standard	TA935-1A (1/4-28 Stud)	TA935-2C / (1/4-28 Stud)		TA935-3C / (1/4-28 Stud)			
			 (length in feet) (termination)		/ - (maximum armor length 100 ft.) (cable length in feet) (termination)		
Metric	M/TA935-1A (M6x1 Adapter Stud)	M/TA935-2C / (M6x1 Adapter Stud)		M/TA935-3C / (M6x1 Adapter Stud)			
			 (length in feet) (termination)		/ - (maximum armor length 100 ft.) (cable length in feet) (termination)		
			 (length in meters) (termination)		M / M - (maximum armor length 30 m) (cable length in meters) (termination)		

Cable Terminations: L  Z 

Read Before Purchasing
Important information on
Regulatory Approvals and Requirements
on Page 87

Tekniset tiedot

- Sensitivity: 100 mV/g
- Frequency Response (± 3 dB): 30-900,000 CPM
- Dynamic Range: ± 80 g, peak
- Power Requirements Voltage Source: 18-28 VDC
- Temperature Range: -40 to 250°F (-40 to 121°C)
- Case Material: 316L Stainless Steel
- Connector: 3 Pin MIL-C-5015
- Max Temp: 250°F (121°C)

Dokumentit

1. [Esite](http://www.mip.fi/images/docs/fi/1_vs_ta935_ds.pdf) , (URL: http://www.mip.fi/images/docs/fi/1_vs_ta935_ds.pdf)

Lisäkuvat ja videot

