

UEB330 ULTRASOUND SENSOR, 100MV/G

Ultrasound Sensor, 100mV/g, Top Exit, 2 Pin mini-MIL Connector, 1/4-28 Mounting

Valmistaja:	CTC
Tuotenumero:	UEB330
Tyyppi:	1-akselinen Teollisuus
Herkkyys:	100 mV/g
Taajuusalue:	0 5-25000 Hz
Mittausalue:	± 50 g

- High Frequency Ultrasound Accelerometer
- High Amplitude Resonance Peak for Stress Wave Measurement Techniques
- IEPE Amplifier Technolog

Tekniset tiedot

- Sensitivity: 100 mV/g
- Frequency Response (±3dB): 30-1,500,000 CPM
- Dynamic Range: ± 50g, peak
- Power Requirements Voltage Source: 18-30 VDC
- Temperature Range: -58 to 250°F
- Case Material: 316L Stainless Steel
- Connector: 2 Pin mini-MIL,
J Series Connector
- Max Temp: 250°F (121°C)

Dokumentit

1. [Esite](http://www.mip.fi/images/docs/fi/ueb330_datasheet.pdf) , (URL: http://www.mip.fi/images/docs/fi/ueb330_datasheet.pdf)

Lisäkuvat ja videot

