

VE135 - PIEZO VELOCITY SENSOR, TOP EXIT CONNECTOR / CABLE, 500 MV/IN/SEC

VE135 - Nopeusanturi, liitäntä päältä/kaapelilla, 500 mV/mm/sec

Valmistaja:	CTC
Tuotenumero:	VE135
Tyyppi:	1-akselinen Teollisuus
Herkkyys:	20 mV/mm/sec
Taajuusalue:	1-10000 Hz
Mittausalue:	±254 mm/sec pk
Sovellukset:	Kunnonvalvonta

Tilausohje:

Ordering Information

Standard	VE135-1A (1/4-28 Stud)	VE135-2C - / (1/4-28 Stud)	VE135-3C - / (1/4-28 Stud)	VE135-6C - / (1/4-28 Stud)
	Stock Product	Build To Order	Build To Order	Build To Order
		(length in feet) (termination)	(maximum armor length 100 ft) (cable length in feet) (termination)	(maximum armor length 20 ft) (cable length in feet) (termination)
Metric	M/VE135-1A (M6x1 Adapter Stud)	M/VE135-2C - / (M6x1 Adapter Stud)	M/VE135-3C - / (M6x1 Adapter Stud)	M/VE135-6C - / (M6x1 Adapter Stud)
	Stock Product	Build To Order	Build To Order	Build To Order
		(length in feet) (termination)	(maximum armor length 100 ft) (cable length in feet) (termination)	(maximum armor length 20 ft) (cable length in feet) (termination)
		(length in meters) (termination)	(maximum armor length 30 m) (cable length in meters) (termination)	(maximum armor length 6 m) (cable length in meters) (termination)

Cable Termination Options: **E**  **F**  **L**  **Z** 

Tekniset tiedot

- Sensitivity: 20 mV/mm/sec
- Frequency Response (±3dB): 1-10000 Hz
- Dynamic Range: ±254 mm/sec. pk
- Power Requirements Voltage Source: 18-30 VDC
- Temperature Range: -58 to 250°F (-50 to 121°C)
- Case Material: 316L Stainless Steel
- Connector: 2 Pin MIL-C-5015
- Max Temp: 250°F (121°C)

Dokumentit

1. [Esite](http://www.mip.fi/images/docs/fi/1_vs_ve135_ds.pdf), (URL: http://www.mip.fi/images/docs/fi/1_vs_ve135_ds.pdf)

Lisäkuvat ja videot

