

VT104 - DUAL OUTPUT PIEZO VELOCITY SENSOR, 4MV/MM/SEC, WITH TEMPERATURE OUTPUT, 10 MV/°C, SIDE EXIT CONNECTOR

VT104 - Dual Output kiihtyvyyssanturi, 4mV/mm/sec, lämpötila ulostulo 10 mV/°C, liitin/kaapeli sivulla

Valmistaja:	CTC
Tuotenumero:	VT104
Tyyppi:	1-akselinen Teollisuus
Herkkyys:	4 mV/mm/sec
Taajuusalue:	1.5-7000 Hz
Mittausalue:	±1270 mm/sec. pk
Sovellukset:	Kunnonvalvonta

Tilausohje:

Ordering Information

Standard	VT104-1D (1/4-28 Captive Bolt) Stock Product	VT104-2D / (1/4-28 Captive Bolt) Build To Order [] [] [] - [] (length in feet) (termination)	VT104-3D / (1/4-28 Captive Bolt) Build To Order [] [] [] / [] [] [] - [] (maximum armor length 100 ft.) (cable length in feet) (termination)
Metric	M/VT104-1D (M6x1 Captive Bolt) Stock Product	M/VT104-2D / (M6x1 Captive Bolt) Build To Order [] [] [] - [] (length in feet) (termination) [] [] [] M - [] (length in meters) (termination)	M/VT104-3D / (M6x1 Captive Bolt) Build To Order [] [] [] / [] [] [] - [] (maximum armor length 100 ft.) (cable length in feet) (termination) [] [] [] M / [] [] [] M - [] (maximum armor length 30 m) (cable length in meters) (termination)

Cable Terminations: L  Z 

Tekniset tiedot

- Sensitivity: 4mV/mm/sec
- Frequency Response (±3dB): 1.5-7000 Hz
- Dynamic Range: ±1270 mm/sec. pk
- Power Requirements Voltage Source: 18-30 VDC

- Temperature Range: -58 to 250°F (-50 to 121°C)
- Case Material: 316L Stainless Steel
- Connector: 3 Pin MIL-C-5015
- Max Temp: 250°F (121°C)

Dokumentit

1. [Esite](http://www.mip.fi/images/docs/fi/1_vs_vt104_ds.pdf) , (URL: http://www.mip.fi/images/docs/fi/1_vs_vt104_ds.pdf)

Lisäkuvat ja videot

