

DX191 - 8 MM BENTLY™ COMPATIBLE PROXIMITY PROBE DRIVER FOR EDDY CURRENT PROBE, 4-20 MA AXIAL APPLICATIONS

DX190 - 8 mm Bently™-yhteensopiva kompakti pyörrevirta-anturi ohjain, 4-20 mA Axial Applications

Valmistaja:	CTC
Tuotenumero:	DX191
Herkkyys:	-7.87 V/mm
Sovellukset:	Liukulaakerin kunnonvalvonta
Tyyppi:	4-20 mA Axial
Halkaisija:	8 mm

Saatavana erilaisilla kokoonpanoilla, kaikki asiakastilauksen pohjalta:

Ordering Information

DX191 - - - -

Full Scale	System Length	Mounting Type	Regulatory Approval
06 = 0.6-0-0.6 mm 25 = 25-0-25 mils	50 = 5.0 meter 90 = 9.0 meter	00 = Panel (Mounting Screws Are Not Included) 01 = DIN 02 = None	00 = CE Certified



Example Part Number: DX191-25-90-01-00

4140 Steel, 25-0-25 mils full scale, 9 meter system length, DIN mount, CE certified

Tekniset tiedot

- Temperature Range: -49°F (-45°C) to 185°F (85°C)
- Linear Range: 10 to 90 mils (.25 - 2.30 mm) @ approximately -1 to -17 VDC
- Nominal Voltage Output: -200 mV/mil (-7.87 V/mm)
- 4-20 mA Output: defined by full scale selection
- Input Power/Voltage: 17.5 VDC to 30 VDC (Loop Powered)
- Aluminum enclosure
- Miniature 12-32 threaded connector
- 4 Position screw terminals + BNC output
- Calibrated to AISI 4140 steel

Dokumentit

1. [Esite](http://www.mip.fi/images/docs/fi/dx191.pdf), (URL: <http://www.mip.fi/images/docs/fi/dx191.pdf>)

Lisäkuvat ja videot

DX191 mitat